



HMA I-LIFT 65

530XX-XXXXX-XXXXXX



The height adjustable industrial suspension arm with full integration in the suspension systems HMA I-080, HMA I-130 and HMA I-225

- Default colours
 - Cover: RAL 7035 (Light grey)
 - Bearings: RAL 7016 (Anthracite grey)
 - Special colours on request
- Vertical swivel angle $\pm 40^\circ$ with continuously variable stroke limiter to $\pm 0^\circ$
- Restraint-guided load suspension at head joint
- Head bearing mounting upwards and downwards possible
- Stroke locking with operator release (option)
- Loading weight from head joint 5-65 kg in 7 weight ranges (TLB)
- Fine adjustment within the load capacity range (TLB) continuously
- Load range exclusive vertical tube and attachments
- Integrated brake
- Low maintenance

Lift length	635 mm	895 mm
Dead weight	18 kg	20 kg
Cable duct	45 x 30 mm	
Vertical stroke	500 mm	900 mm
Loading weight range	0 - 0 kg	0 - 0 kg

HMA I-LIFT 65-1 (635 MM)

5302X-71XXX-XXXXXXX



The height adjustable industrial suspension arm from 5 - 65 kg with 635 mm lift length connectable via bottom head joint

- Vertical swivel angle +/- 40° with continuously variable stroke limiter to +/- 0°
- Restraint-guided load suspension at head joint
- Head bearing mounting upwards and downwards possible
- Stroke locking with operator release (option)
- Full integration in the suspension systems HMA I-080, HMA I-130 and HMA I-225
- Loading weight from head joint 5-65 kg in 7 weight ranges (TLB)
- Fine adjustment within the load capacity range (TLB) continuously
- Integrated brake
- Dead weight: 18 kg

Product code	Description
53021-71100-8707110	HMA I-Lift 65-1, 635 mm, TLB 5-10 kg, Colours: RAL 7016, RAL 7035
53021-71200-8707110	HMA I-Lift 65-1, 635 mm, TLB 5-10 kg, lockable, Colours: RAL 7016, RAL 7035
53022-71100-8707110	HMA I-Lift 65-1, 635 mm, TLB 9-14 kg, Colours: RAL 7016, RAL 7035
53022-71200-8707110	HMA I-Lift 65-1, 635 mm, TLB 9-14 kg, lockable, Colours: RAL 7016, RAL 7035
53023-71100-8707110	HMA I-Lift 65-1, 635 mm, TLB 13-20 kg, Colours: RAL 7016, RAL 7035
53023-71200-8707110	HMA I-Lift 65-1, 635 mm, TLB 13-20 kg, lockable, Colours: RAL 7016, RAL 7035
53024-71100-8707110	HMA I-Lift 65-1, 635 mm, TLB 19-27 kg, Colours: RAL 7016, RAL 7035
53024-71200-8707110	HMA I-Lift 65-1, 635 mm, TLB 19-27 kg, lockable, Colours: RAL 7016, RAL 7035
53025-71100-8707110	HMA I-Lift 65-1, 635 mm, TLB 26-37 kg, Colours: RAL 7016, RAL 7035
53025-71200-8707110	HMA I-Lift 65-1, 635 mm, TLB 26-37 kg, lockable, Colours: RAL 7016, RAL 7035
53026-71100-8707110	HMA I-Lift 65-1, 635 mm, TLB 36-52 kg, Colours: RAL 7016, RAL 7035
53026-71200-8707110	HMA I-Lift 65-1, 635 mm, TLB 36-52 kg, lockable, Colours: RAL 7016, RAL 7035
53027-71100-8707110	HMA I-Lift 65-1, 635 mm, TLB 51-65 kg, Colours: RAL 7016, RAL 7035
53027-71200-8707110	HMA I-Lift 65-1, 635 mm, TLB 51-65 kg, lockable, Colours: RAL 7016, RAL 7035

HMA I-LIFT 65-2 (635 MM)

5302X-72XXX-XXXXXXX



The height adjustable industrial suspension arm from 5 - 65 kg with 635 mm lift length connectable via top head joint

- Vertical swivel angle +/- 40° with continuously variable stroke limiter to +/- 0°
- Restraint-guided load suspension at head joint
- Head bearing mounting upwards and downwards possible
- Stroke locking with operator release (option)
- Full integration in the suspension systems HMA I-080, HMA I-130 and HMA I-225
- Loading weight from head joint 5-65 kg in 7 weight ranges (TLB)
- Fine adjustment within the load capacity range (TLB) continuously
- Integrated brake
- Dead weight: 18 kg

Product code	Description
53021-72100-8707110	HMA I-Lift 65-2, 635 mm, TLB 5-10 kg, Colours: RAL 7016, RAL 7035
53021-72200-8707110	HMA I-Lift 65-2, 635 mm, TLB 5-10 kg, lockable, Colours: RAL 7016, RAL 7035
53022-72100-8707110	HMA I-Lift 65-2, 635 mm, TLB 9-14 kg, Colours: RAL 7016, RAL 7035
53022-72200-8707110	HMA I-Lift 65-2, 635 mm, TLB 9-14 kg, lockable, Colours: RAL 7016, RAL 7035
53023-72100-8707110	HMA I-Lift 65-2, 635 mm, TLB 13-20 kg, Colours: RAL 7016, RAL 7035
53023-72200-8707110	HMA I-Lift 65-2, 635 mm, TLB 13-20 kg, lockable, Colours: RAL 7016, RAL 7035
53024-72100-8707110	HMA I-Lift 65-2, 635 mm, TLB 19-27 kg, Colours: RAL 7016, RAL 7035
53024-72200-8707110	HMA I-Lift 65-2, 635 mm, TLB 19-27 kg, lockable, Colours: RAL 7016, RAL 7035
53025-72100-8707110	HMA I-Lift 65-2, 635 mm, TLB 26-37 kg, Colours: RAL 7016, RAL 7035
53025-72200-8707110	HMA I-Lift 65-2, 635 mm, TLB 26-37 kg, lockable, Colours: RAL 7016, RAL 7035
53026-72100-8707110	HMA I-Lift 65-2, 635 mm, TLB 36-52 kg, Colours: RAL 7016, RAL 7035
53026-72200-8707110	HMA I-Lift 65-2, 635 mm, TLB 36-52 kg, lockable, Colours: RAL 7016, RAL 7035
53027-72100-8707110	HMA I-Lift 65-2, 635 mm, TLB 51-65 kg, Colours: RAL 7016, RAL 7035
53027-72200-8707110	HMA I-Lift 65-2, 635 mm, TLB 51-65 kg, lockable, Colours: RAL 7016, RAL 7035

HMA I-LIFT 65-1 (895 MM)

5305X-71XXX-XXXXXXX



The height adjustable industrial suspension arm from 5 - 65 kg with 895 mm lift length connectable via bottom head joint

- Vertical swivel angle +/- 40° with continuously variable stroke limiter to +/- 0°
- Restraint-guided load suspension at head joint
- Head bearing mounting upwards and downwards possible
- Stroke locking with operator release (option)
- Full integration in the suspension systems HMA I-080, HMA I-130 and HMA I-225
- Loading weight from head joint 5-65 kg in 7 weight ranges (TLB)
- Fine adjustment within the load capacity range (TLB) continuously
- Integrated brake
- Dead weight: 20 kg

Product code	Description
53051-71100-8707110	HMA I-Lift 65-1, 895 mm, TLB 5-10 kg, Colours: RAL 7016, RAL 7035
53051-71200-8707110	HMA I-Lift 65-1, 895 mm, TLB 5-10 kg, lockable, Colours: RAL 7016, RAL 7035
53052-71100-8707110	HMA I-Lift 65-1, 895 mm, TLB 9-14 kg, Colours: RAL 7016, RAL 7035
53052-71200-8707110	HMA I-Lift 65-1, 895 mm, TLB 9-14 kg, lockable, Colours: RAL 7016, RAL 7035
53053-71100-8707110	HMA I-Lift 65-1, 895 mm, TLB 13-20 kg, Colours: RAL 7016, RAL 7035
53053-71200-8707110	HMA I-Lift 65-1, 895 mm, TLB 13-20 kg, lockable, Colours: RAL 7016, RAL 7035
53054-71100-8707110	HMA I-Lift 65-1, 895 mm, TLB 19-27 kg, Colours: RAL 7016, RAL 7035
53054-71200-8707110	HMA I-Lift 65-1, 895 mm, TLB 19-27 kg, lockable, Colours: RAL 7016, RAL 7035
53055-71100-8707110	HMA I-Lift 65-1, 895 mm, TLB 26-37 kg, Colours: RAL 7016, RAL 7035
53055-71200-8707110	HMA I-Lift 65-1, 895 mm, TLB 26-37 kg, lockable, Colours: RAL 7016, RAL 7035
53056-71100-8707110	HMA I-Lift 65-1, 895 mm, TLB 36-52 kg, Colours: RAL 7016, RAL 7035
53056-71200-8707110	HMA I-Lift 65-1, 895 mm, TLB 36-52 kg, lockable, Colours: RAL 7016, RAL 7035
53057-71100-8707110	HMA I-Lift 65-1, 895 mm, TLB 51-65 kg, Colours: RAL 7016, RAL 7035
53057-71200-8707110	HMA I-Lift 65-1, 895 mm, TLB 51-65 kg, lockable, Colours: RAL 7016, RAL 7035

HMA I-LIFT 65-2 (895 MM)

5305X-72XXX-XXXXXXXX



The height adjustable industrial suspension arm from 5 - 65 kg with 895 mm lift length connectable via top head joint

- Vertical swivel angle +/- 40° with continuously variable stroke limiter to +/- 0°
- Restraint-guided load suspension at head joint
- Head bearing mounting upwards and downwards possible
- Stroke locking with operator release (option)
- Full integration in the suspension systems HMA I-080, HMA I-130 and HMA I-225
- Loading weight from head joint 5-65 kg in 7 weight ranges (TLB)
- Fine adjustment within the load capacity range (TLB) continuously
- Integrated brake
- Dead weight: 20 kg

Product code	Description
53051-72100-8707110	HMA I-Lift 65-2, 895 mm, TLB 5-10 kg, Colours: RAL 7016, RAL 7035
53051-72200-8707110	HMA I-Lift 65-2, 895 mm, TLB 5-10 kg, lockable, Colours: RAL 7016, RAL 7035
53052-72100-8707110	HMA I-Lift 65-2, 895 mm, TLB 9-14 kg, Colours: RAL 7016, RAL 7035
53052-72200-8707110	HMA I-Lift 65-2, 895 mm, TLB 9-14 kg, lockable, Colours: RAL 7016, RAL 7035
53053-72100-8707110	HMA I-Lift 65-2, 895 mm, TLB 13-20 kg, Colours: RAL 7016, RAL 7035
53053-72200-8707110	HMA I-Lift 65-2, 895 mm, TLB 13-20 kg, lockable, Colours: RAL 7016, RAL 7035
53054-72100-8707110	HMA I-Lift 65-2, 895 mm, TLB 19-27 kg, Colours: RAL 7016, RAL 7035
53054-72200-8707110	HMA I-Lift 65-2, 895 mm, TLB 19-27 kg, lockable, Colours: RAL 7016, RAL 7035
53055-72100-8707110	HMA I-Lift 65-2, 895 mm, TLB 26-37 kg, Colours: RAL 7016, RAL 7035
53055-72200-8707110	HMA I-Lift 65-2, 895 mm, TLB 26-37 kg, lockable, Colours: RAL 7016, RAL 7035
53056-72100-8707110	HMA I-Lift 65-2, 895 mm, TLB 36-52 kg, Colours: RAL 7016, RAL 7035
53056-72200-8707110	HMA I-Lift 65-2, 895 mm, TLB 36-52 kg, lockable, Colours: RAL 7016, RAL 7035
53057-72100-8707110	HMA I-Lift 65-2, 895 mm, TLB 51-65 kg, Colours: RAL 7016, RAL 7035
53057-72200-8707110	HMA I-Lift 65-2, 895 mm, TLB 51-65 kg, lockable, Colours: RAL 7016, RAL 7035